

# IMPERIAL AXMINSTER\*





33716/118 CLARET



33716/118 CLARET

**CUT PILE PATTERNED**

*Please note: There may be slight color difference between the picture and actual carpet.*

IMPERIAL AXMINSTER - 33716/138 NIGHT SKY  
Carpet Raya Office@JB, Malaysia



33716/138 NIGHT SKY  
Pin Si Restaurant @ Yishun, Singapore



3716/118 CLARET



3716/138 NIGHT SKY

Kindly check stock availability with us before confirming the order. \*Discontinued design.

**IMPERIAL AXMINSTER**

# IMPERIAL AXMINSTER\*



3716-118 CLARET



3716-138 NIGHT SKY

## IMPERIAL AXMINSTER Specifications

Construction	Gripper Axminster
Yarn Composition	80% Pure New Wool, 20% Nylon
Pitch per inch	7 inch
Rows per inch	8 inch
Tufted Pile Weight	Ca. 1300 g/m <sup>2</sup> (38 oz/yd <sup>2</sup> )
Total Weight	Ca. 2230 g/m <sup>2</sup> (66 oz/yd <sup>2</sup> )
Pile Height	Ca. 8.5 mm (+/- 0.5 mm)
Total Height	Ca. 10.5 mm (+/- 0.5 mm)
Standard Roll Size	4m x 30m
Pattern Repeat Size	1m x 1m

## Performance (as tested by ITTS Inc. USA)

Stain Resistance	6 (AATCC-175-1993)
Static Control	Pass - Max. 4 kV (AATCC 134-1996)
Tuft Bind	Pass - 5.3 lbs (ASTM-D-1335)
Dimensional Stability	Pass - Max. 0.25% change (AACHEN)
Flammability	
- Pill Test	Pass - 8 (ASTM-D-2859-96) (FF 1-70)
- Radiant Panel	Pass - Class I (ASTM-E-648-06)
- Smoke Density	Pass - Max. 450 (ASTM-E-662-03)
Colourfastness	
- to light	Excellent - 5 (AATCC-16E)
- to wet & dry cleaning	Excellent - 5 (AATCC-165)
- to ozone	Excellent - 5 (AATCC-129)

## Warranties

10 Year Carpet Wear Warranty

Lifetime Antishock Carpet Warranty

Ideal for Medium to Heavy Hospitality Use.

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing. Where seaming is necessary, a seam sealant must be used for all such installations. Due to dye lot variations, actual color may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.

Installation Instruction    Underlay and Gripper Rods

