



VIEW ON WEBSITE



SCAN HERE ↑

LIVING STONE*



1512 BASANITE

CUT PILE PATTERNED

Please note: There may be slight color difference between the picture and actual carpet. Slight color variation may occur from dye lot to dye lot.



1556 BOX BITE



1525 OPAL HONEY



1547 CLOVERSTONE

1556 BOX BITE

LIVINGSTONE Specifications

Construction	1/10" Tip Sheared Loop Pattern
Yarn Composition	100% Avalor® SD Nylon with Puralex®
Tufted Pile Weight	Ca. 1085 g/m ² (32 oz/yd ²) (+/- 10%)
Total Weight	Ca. 2332 g/m ² (68.8 oz/yd ²) (+/- 10%)
Pile Height	Ca. 2.38 mm (0.094 in) (min), Ca. 8.73 mm (0.344 in) (max)
Average Pile Thickness	Ca. 3.1 mm
Total Maximum Thickness	Ca. 9.5 mm (0.375 in)
Stitch Rate	51.2 per 10 cm (13 S.P.I.)
Average Density	8,195 (17.2 Kilotex/cm ²)
Backing	Woven Synthetic
Standard Roll Size	3.66m (+/-2%) x 45.72m (+/-2%)
Pattern Repeat Size	30.5 cm (W) x 39 cm (L) (12" x 15.4")

Performance (as tested by ITTS Inc. USA)

Stain Resistance	10 (AATCC-175), Commercial Stain Protection
Static Control	Pass - Max. 3 kV (AATCC 134-1996)
Soil Resistance	Commercial Anti-Soil Protection
Tuft Bind	Pass - 8.6 lbs (ASTM-D-1335)
Flammability	
- Pill Test	Pass - 8 (ASTM-D-2859-96)
- Radiant Panel	Pass - Class I (ASTM E-648-06)
- Smoke Density	Pass - Max. 450 (ASTM-E-662-03)
Colourfastness to light	Excellent - 5 (AATCC-16E)

Warranties

- 10 Year Carpet Wear Warranty
- Lifetime Limited Stain Warranty
- Lifetime Limited Static Warranty
- Lifetime Limited Colorfastness Warranty

Ideal for Heavy Commercial and Hospitality Use.

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing. Where seaming is necessary, a seam sealant must be used for all such installations. Due to dye lot variations, actual color may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.

MANUFACTURED IN USA

- **Reduces Odors**
Breaks down almost any indoor odour

- **Freshens the Air**
Breaks down organic molecules into inert materials and attacks virtually all odors.

- **Environmentally Friendly with no harmful chemicals**
Salt compound - a mixture of organic and inorganic ingredients.

- **Reduces VOC's in the Room Environment**
Puralex® helps reduce volatile organic compounds by absorbing odors from the indoor air as shown in independent testing using EPA approved methods.

- **Self Renewing**
Puralex® renews itself through contact with air circulation.

- **Safety and Performance Life**
Passes all standards of safety and performance. Testing confirms the Puralex® activates by air circulation and withstands both repeated cleanings and wear.

Puralex®



LIVINGSTONE