

Nice

Control electronics

control units

Concealed control system TAG	recessed transmitter powered by mains electricity		TTX4	→	page 56	
		recessed transmitter, battery-powered		TTXB4	→	page 56
	miniaturised receiver, for mounting on a wall-plate	for dry contact controlled motors, 4-wire motors and lights		TT2Z	→	page 57
		for 1 light or 230 Vac load, with internal switching module		TT2D	→	page 58
	miniaturised receiver, for passthrough installation	for Venetian blinds, to control motors up to 500 W. 433.92 MHz receiver, rolling code		TT1V	→	page 59
		to control loads at 230 Vac mains voltage with power up to 500 W. 433.92 MHz frequency receiver, rolling code		TT1L	→	page 59
		with Hirschmann connector to control one motor up to 500 W for outdoor Venetian blinds, sun awnings and rolling shutters. 433.92 MHz frequency receiver, rolling code		TT1VR	→	page 60

Surface mounted control units
with Wind-Sun levels adjustable
by transmitter or trimmer
MINDY TT

- to control 1 motor up to 1000 W. Adjustment of climatic sensors by trimmer **TT3** → page 61
- to control 1 motor up to 1000 W. 433.92 MHz receiver, rolling code. Adjustment of climatic sensors by trimmer **TT4** → page 61
- to control 2 synchronised motors up to 600 W. 433.92 MHz receiver, rolling code. Adjustment of climatic sensors by trimmer **TT5** → page 61

Communication interface

- TTBus-RS232 and control unit for tubular motors **TT6** → page 62

programming units

Programmiers

- for Nice tubular motors with dry contact or TTBus technology **TTPRO BD** → page 65
- for Nice tubular motors with electronic limit switch **TTU** → page 66

Nice

Serie Domì New

New generation of transmitters designed for every needs.

The transmitters in the Domì series have a uniform design: your customers can choose between **two colour variants**, white and totally black and can decide upon the desired functions. All models have a **high-quality finish**, provide **comfortable operation** and **blend harmoniously** into any home, office or hotel.

Be it mini-transmitters, wall-mounted transmitters or hand-held radio transmitters... the controls in the Domì series take care of visual and sun protection simply and comfortably.



Domì P, hand-held radio transmitter:



Domì P1
Single channel, with key to verify automation status, in white and black.



Domì P6
6-channel, with key to verify automation status, in white and black.



Domì P1SV
Single channel, with slider, key for sun on/off and key to verify automation status, in white and black.



Domì P6SV
6-channel, with slider, key for sun on/off and key to verify automation status, in white and black.



Domì P18V
18 channels with display, slider, Sun on/off and partial position button, in white and black.

MiniDomì, hand-held radio transmitter:



MiniDomì 1
Single channel, with key to verify the automation status, in white and black.



MiniDomì 6
6-channel, with key to verify the automation status, in white and black.

Domì W, wall-mounted radio transmitter:



Domì W1
Single-channel, with key to verify the automation status, in white and black.



Domì W6
6-channel, with key to verify the automation status, in white and black.

Nice

Domì P1 New

Portable 1 channel bidirectional radio transmitter.



Wall bracket

Domì P1 is a single-channel hand-held radio transmitter. It can be used as a single, group or central control.

The elegant control is available in the colours **white and black.**

A wall bracket is included in the delivery scope.

Transmission and feedback commands are visualised.

Code	Description	Quantity	Conformity
DOMIP1	Portable 1 channel bidirectional transmitter white	1	CE
DOMIP1B	Portable 1 channel bidirectional transmitter black	1	CE

TECHNICAL DATA

Code	DOMIP1, DOMIP1B
Battery type (V)	2 x AAA
Battery life (years)	~3 (with 10 transmission commands/day)
Radio frequency (MHz)	433.92
Transmitter RF power (ERP)	≤ 10 dBm
Number of groups	1
Radio coding	BD (PLN2+) or mono (O-Code TTS)
Ambient operating temperature (°C)	-5 to 55
Relative humidity	max. 85% (not for wet rooms, non-condensing)
Ingress protection (IP)	40
Weight incl. batteries (g)	75
Dimensions (mm)	155x43x23
Installation (optional)	wall-mounted
Conformity	CE



ONE CHANNEL



ERGONOMIC

BiDi

Yubii

433 MHz

Nice

Domì P6

New

Portable 6 channel bidirectional radio transmitter.



Wall bracket

Domì P6 is a 6-channels hand-held radio transmitter. It is able to manage up to 6 groups of automations in single, group or multigroup mode.

The elegant control is available in the colours white and black.

A wall bracket is included in the delivery scope.

Transmission and feedback commands are visualised.

Code	Description	Quantity	Conformity
DOMIP6	Portable 6 channels bidirectional transmitter white	1	CE
DOMIP6B	Portable 6 channels bidirectional transmitter black	1	CE

TECHNICAL DATA

Code	DOMIP6, DOMIP6B
Battery type (V)	2 x AAA
Battery life (years)	~ 3 (with 10 transmission commands/day)
Radio frequency (MHz)	433.92
Transmitter RF power (ERP)	≤ 10 dBm
Number of groups	6
Radio coding	BD (PLN2+) or mono (O-Code TTS)
Ambient operating temperature (°C)	-5 to 55
Relative humidity	max. 85% (not for wet rooms, non-condensing)
Ingress protection (IP)	40
Weight incl. batteries (g)	75
Dimensions (mm)	155x43x23
Installation (optional)	wall-mounted
Conformity	CE



SIX CHANNELS



ERGONOMIC

BiDi

Yubii

433 MHz

Nice

Domì P1 SV New

Portable 1 channel bidirectional radio transmitter with slider and Sun On/Off.



Wall bracket

Domì P1SV is a single-channel hand-held radio transmitter. It can be used as a single, group or central control.

Transmission and feedback commands are visualised.

The elegant control is available in the colours **white and black**.

Using the slider, lighting can be **dimmed steplessly**, for example, or a radiant heater can be adjusted if these are fitted with suitable **Nice radio receivers**.

A wall bracket is included in the delivery scope.

Code	Description	Quantity	Conformity
DOMIP1SV	Portable 1 channel bidi transmitter white with slider and Sun On/Off	1	CE
DOMIP1SVB	Portable 1 channel bidi transmitter black with slider and Sun On/Off	1	CE

TECHNICAL DATA

Code	DOMIP1SV, DOMIP1SVB
Battery type (V)	2 x AAA
Battery life (years)	~3 (with 10 transmission commands/day)
Radio frequency (MHz)	433.92
Transmitter RF power (ERP)	≤ 10 dBm
Number of groups	1
Radio coding	BD (PLN2+) or mono (O-Code TTS)
Ambient operating temperature (°C)	-5 to 55
Relative humidity	max. 85% (not for wet rooms, non-condensing)
Ingress protection (IP)	40
Weight incl. batteries (g)	75
Dimensions (mm)	155x43x23
Installation (optional)	wall-mounted
Conformity	CE



ONE CHANNEL



ERGONOMIC



SLIDER



SUN ON/OFF

BiDi

Yubii

433 MHz

Nice

Domì P6 SV New

Portable 6 channel bidirectional radio transmitter with slider and Sun On/Off.



Wall bracket

- SIX CHANNELS
- ERGONOMIC
- SLIDER
- SUN ON/OFF

- BiDi
- Yubii
- 433 MHz

Domì P6SV is a 6-channel hand-held radio transmitter. It is able to manage up to 6 groups of automations in single, group or multigroup mode.

Transmission and feedback commands are visualised.

The elegant control is available in the colours **white and black.**

Using the slider, lighting can be dimmed steplessly, for example, or a radiant heater can be adjusted if these are fitted with suitable **Nice radio receivers.**

A wall bracket is included in the delivery scope.

Code	Description	Quantity	Conformity
DOMIP6SV	Portable 6 channel bidi transmitter white with slider and Sun On/Off	1	CE
DOMIP6SVB	Portable 6 channel bidi transmitter black with slider and Sun On/Off	1	CE

TECHNICAL DATA

Code	DOMIP6SV, DOMIP6SVB
Battery type (V)	2 x AAA
Battery life (years)	~ 3 (with 10 transmission commands/day)
Radio frequency (MHz)	433.92
Transmitter RF power (ERP)	≤ 10 dBm
Number of groups	6
Radio coding	BD (PLN2+) or mono (O-Code TTS)
Ambient operating temperature (°C)	-5 to 55
Relative humidity	max. 85% (not for wet rooms, non-condensing)
Ingress protection (IP)	40
Weight incl. batteries (g)	75
Dimensions (mm)	155x43x23
Installation (optional)	wall-mounted
Conformity	CE

Nice

Domì P18V New

Portable 18 channels bidirectional radio transmitter with display, slider and partial position button.



Wall bracket

Domì P18V is a 18-channel hand-held radio transmitter. It is able to manage up to 18 motors in single way.

Using the slider, lighting can be dimmed steplessly, for example, or a radiant heater can be adjusted if these are fitted with suitable **Nice radio receivers.**

Transmission and feedback commands are visualised.

A wall bracket is included in the delivery scope.

The elegant control is available in the colours **white and black.**

Code	Description	Quantity	Conformity
DOMIP18V	Portable 18 channel bidi transmitter white with slider	1	CE
DOMIP18VB	Portable 18 channel bidi transmitter black with slider	1	CE

TECHNICAL DATA

Code	DOMIP18V, DOMIP18VB
Battery type (V)	2 x AAA
Battery life (years)	~ 3 (with 10 transmission commands/day)
Radio frequency (MHz)	433.92
Transmitter RF power (ERP)	≤ 10 dBm
Number of groups	18
Radio coding	BD (PLN2+) or mono (O-Code TTS)
Ambient operating temperature (°C)	-5 to 55
Relative humidity	max. 85% (not for wet rooms, non-condensing)
Ingress protection (IP)	40
Weight incl. batteries (g)	75
Dimensions (mm)	155x43x23
Installation (optional)	wall-mounted
Conformity	CE



EIGHTEEN CHANNELS



ERGONOMIC



SLIDER



SUN ON/OFF

BiDi

Yubii

433 MHz

Ergonomic operation, simple teaching-in.

The transmitters in the Domì series are attractive, easy to operate and, moreover, very easy to teach in.

In addition to the programming keys, they have a “Sun for You” function. This makes it possible to determine the status of the sun sensors and to de-/activate them.