







TECHNICAL INFORMATION

Installation Guide

- The subfloor surfaces must be level, flat, clean, dry, smooth, and free of movement. All surface imperfections should be filled and sanded with a portland cement-based latex patching compound.
- Room temperature must be maintained at 18℃ or higer before and during installation.
- The flooring must be allowed to acclimate in the room to be installed for a minimum of 24 hours and be stacked flat on the floor to avoid bending the floor.
- Prior to installation, please ensure that both color and lot # are the same.

Maintenance

- Regularly sweep floor to remove sand and grit that can scratch floor.
- For best results, use only water with a mop. Avoid flooding the floor with too much water.
- For heavily soiled areas, use a neutral ph balanced floor cleaner.
- Use caution when lifting boxes.
- Promptly remove any standing water to avoid slippage.
- Keep Infiniti on the flat surface to keep it from warping.

Technical Data

DESCRIPTION	Standard	Wood	Stone	Carpet
Total thickness	EN 428	2.0mm	2.0mm	2.0mm
Wear layer thickness	EN 429	0.2mm	0.2mm	0.2mm
Total weight	EN 430	3450g/m^2	3450g/m^2	3450g/m^2
Size	EN 427	152.4×914.4mm	457.2×457.2mm	457.2×457.2mm
	ASTM F 536	6"×36"	18"×18"	18"×18"
CLASSIFICATION				
Classification	EN 685	23-31	23-31	23-31
Fire rating	EN 13501-1	Bfl-s1	Bfl-s1	Bfl-s1
Static electrical propensity	EN 1815	<2kV	<2kV	<2kV
Slip resistance wet	DIN 51130	R9	R9	R10
PERFORMANCES				
Wear resistance	EN 660-2	≤2.0mm^3	≤2.0mm^3	≤2.0mm^3
Wear group	NF 189	Group T	Group T	Group T
Impact sound reduction	EN ISO 717-2	5dB	5dB	5dB
Residual indentation	EN 433	≤0.10mm	≤0.10mm	≤0.10mm
Castor chair	EN 425	OK	OK	OK
Thermal resistance	EN 12524	0.25W/(m.K)	0.25W/(m.K)	0.25W/(m.K)
Colour fastness	EN 20 105-B02	≥6	≥6	≥6
Surface treatment	---	PUR	PUR	PUR
Chemical resistance	EN 423	Good	Good	Good
CE MARKING				
CE MARKING CE	EN 14041			

Infiniti

LUXURY VINYL TILES



Infiniti

18" x 18"
457.2 x 457.2 mm IN STOCK

600 x 600 mm (MOQ 1000m²)


3310


3301


3303


3334


3335


3314


6604


6605


6603

Infiniti

6" x 36"
152.4 x 914.4 mm IN STOCK

7" x 48"
177.8 x 1219.2 mm (MOQ 1000m²)


9901


9903


9904


9905


9906


9910


9911


9912


9913


9917


9918


9919